Deep Offshore Developments – Subsea / Topsides Integrated Approach

Luc Hême de Lacotte, Audrey Lopez – TECHNIP Luc Rivière, Jérôme Anfray - TOTAL







SUMMARY

- 1. Subsea Processing Integrated Methodology
- 2. Case Study Description
 - a. Conventional Architecture
 - b. Advanced Architecture
- 3. Subsea Processing Selection
- 4. Impact on other packages

Flowlines Design
Subsea Layout
Electrical and Umbilical
Floating Facilities and Topsides Layout

5. Availability, Schedule and Cost elements











SUBSEA PROCESSING - INTEGRATED METHODOLOGY





CONVENTIONAL ARCHITECTURE (W/O SUBSEA PROCESSING)


proven and approved technologies for FPSO, subsea flowlines and risers





ADVANCED ARCHITECTURE (WITH SUBSEA PROCESSING)

cutting edge approach encompassing advanced industry approved components and technologies





SUBSEA PROCESSING SELECTION

- ☐ Choice based on following Criteria
 - Technologies mature in 2020, modules weight limited to 400t
 - Selection criteria: HSE, Cost, Performance, Operation, Project execution
- ☐ Main Selection drivers and impacts



Sanarator

- Located at riser base with gas free flowing to the Topsides
- Pressure selected to minimise Topsides Compression and Subsea Boosting
- More flexible operations

Pump

- Selection of an Hybrid pump for all operations
- Removal of Gas Lift requirement
- Impact on the Umbilical (control, fluids, electrical)






Chemical Storage and Injection

- Located close to the Satellite Wells
- Impact on Umbilicals, Electrical and Topsides facilities designs

Seawater treatment and injection

- Located close to the Water Injection Wells
- Impact on Riser, Flowlines and Topsides facilities design





FLOWLINES DESIGN

	CONVENTIONAL	ADVANCED
Main Field	Loop Lines 2 x 2 x 8" ID Wet insulated	Single Line 2 x 1 x 8" ID Wet insulated & active heating
Satellite Field	Hybrid Loop Lines 1 x 12" ID PiP 1 x 12" ID service line	Single Line 1 x 9" ID Wet insulated & active heating

ADVANCED ARCHITECTURE:

OPERATION Philosophy

- Intermittent heating (Main Field)
- Continuous heating (Satellite)

TECHNOLOGY - Active Heating

- DEH wet insulated single pipe
 - Trace Heated Single Pipe




Best Thermal management
Easier Operation: shutdown, restart, preservation
Reduction of Subsea Lines and Sizes



SUBSEA LAYOUT - RISER BASE

ADVANCED ARCHITECTURE:







ELECTRICAL and UMBILICAL SYSTEMS

	CONVENTIONAL	ADVANCED
Subsea Power Requirement	Only control	SSP Equipment, Active Heating, Control 15 MW Main Field 7 MW Satellite
Umbilical Main Field	1 x 5" OD – Wellhead	1 x 5" OD – Wellhead 1 x 7" OD – Active Heating 2 x 6" OD – SSP Equipment
Umbilical Satellite	1 x 9" OD – Wellhead	1 x 6" OD – Power Cable to Tie-back + Wellhead 1 x 8" OD – SSP Equipment + Active Heating

ADVANCED ARCHITECTURE:

Main Field

- No Electrical showstopper
- Power through Umbilicals


Satellite

- Long Distance Transport
- Flowline Active Heating
 - Simplified Umbilical



FLOATING FACILITY AND LAYOUT

□ Conventional Architecture



□ Advanced Architecture



REMOVED

- SW treatment
- 1st stage separator
- Oil circulation
- Gas Lift

- Utilities

INCREASED

- 2nd stage separator
- MP Compression
- REDUCED
- Water Injection
- HP Compression
- Flare

ADVANCED ARCHITECTURE:

Reduction in Hull size (up to 30m) Reduction in Topsides weights (-12%)



AVAILABILITY, SCHEDULE AND COST ELEMENTS

ADVANCED ARCHITECTURE:

□ Availability

Subsea Processing equipment failure has minimal impact on the global production availability (RAM study)

☐ Project Schedule

FPSO construction time can be reduced due to less Topside

□ Cost elements

- Equivalent global CAPEX compared to the conventional Architecture but SSP costs could be optimised
- ii. Cost savings with:

SURF Main Field: -13%
SURF Satellite Field: -30%
FPSO: -10%

iii. Potentially increased reserves thanks to lower subsea tie-in pressure




CONCLUSION

- □ Advanced subsea architectures including Subsea Processing and Active Heating are economic enablers for developing deepwater fields and very long tie-backs.
- □ Integration of Subsea Processing equipment brings the following benefits compared to a conventional approach:
 - **❖** Simplified SURF system combined with active heating
 - **❖** Smaller and lighter FPSO
 - **❖** More flexible operations
 - ❖ Increase of Reserves with the Subsea Separation & Boosting
- ☐ Subsea / Topside integrated approach is paramount for a project's success
- ☐ Opportunities for a « full subsea to shore » project are currently investigated



SUBSEA TO SHORE PERSPECTIVE





Subsea to Shore Concept without floater support is being studied

We would like to extend our thanks to Technip and Total, for giving us the opportunity and encouragement to carry out this project.

Furthermore, we would like to recognize all of those who contributed, directly or indirectly, to this work.

Questions?

